

Five-Year Limited Warranty

This Oben product is warranted to the original purchaser to be free from defects in materials and workmanship under normal consumer use for a period of five (5) years from the original purchase date or thirty (30) days after replacement, whichever occurs later. The warranty provider's responsibility with respect to this limited warranty shall be limited solely to repair or replacement, at the provider's discretion, of any product that fails during normal use of this product in its intended manner and in its intended environment. Inoperability of the product or part(s) shall be determined by the warranty provider. If the product has been discontinued, the warranty provider reserves the right to replace it with a model of equivalent quality and function. This warranty does not cover damage or defect caused by misuse, neglect, accident, alteration, abuse, improper installation or maintenance.

EXCEPT AS PROVIDED HEREIN, THE WARRANTY PROVIDER MAKES NEITHER ANY EXPRESS WARRANTIES NOR ANY IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This warranty provides you with specific legal rights, and you may also have additional rights that vary from state to state. To obtain warranty coverage, contact the Oben Customer Service Department to obtain a return merchandise authorization ("RMA") number, and return the defective product to Oben along with the RMA number and proof of purchase. Shipment of the defective product is at the purchaser's own risk and expense.

For more information or to arrange service, visit www.ObenSupports.com or call Customer Service at 212-594-2353.



Product warranty provided by the Gradus Group.
www.gradusgroup.com

Oben is a registered trademark of the Gradus Group.
© 2025 Gradus Group LLC. All Rights Reserved.

GG2



IBH-11L

Inverted Ballhead



You're on steady ground®

Thank you for choosing Oben.

The Oben IBH-11L Inverted Ballhead is an ideal photo and video accessory for capturing perfect panoramic shots. The inverted design places the ballhead above the base and makes it easy to align your camera with the horizon. Placing the panning base above the ball ensures a camera pan will always remain level. The IBH-11L is equipped with a 1/4-20 mounting socket that's compatible with tripods that have a 1/4-20 screw.


Specifications

Maximum Load	11 lb. (5 kg)	Base Mount	1/4-20
Material	Aluminum	Camera Mount	1/4-20
Vertical Tilt	90°	Height	2.2 in. (6 cm)
Panning Range	360°	Weight	3.75 oz. (106 g)

Precautions

- Do not exceed the ballhead's maximum load capacity (see Specifications).
- Ensure that all appropriate locks are engaged when necessary.
- This ballhead should be used only in temperatures between -22°F and 140°F (-30°C and 60°C).

Overview



1. Bubble level

Use the bubble level to make sure the panoramic base is level with the horizon.

2. 1/4-20 camera mounting screw

Tighten the quick release plate to a camera with the D-ring, a coin, or a flat screwdriver.

3. Arca-type quick-release plate

The Arca-type quick-release plate attaches to the base of your camera with the 1/4-20 mounting screw.

Important! Make sure the plate is seated flush against the base of the clamp before tightening the quick-release collar.

- Remove the camera from the ballhead during transport.
- To avoid damage, always support your device or camera with one hand while adjusting tilt and pan settings.
- All images are for illustrative purposes only.

4. Quick-release locking ring

Turn the ring clockwise to clamp and counterclockwise to remove the quick-release plate.

5. Pan lock

Turn the knob counterclockwise to unlock the panning base. Rotate the base to the desired position and lock it by turning the knob clockwise.

6. 90° notch

Use the notch to instantly switch your camera from landscape to portrait orientation, or to point the camera down at a 90° angle.

7. 1/4-20 mounting socket

Screw the inverted ballhead into a tripod or stand with a 1/4-20 mounting screw.

8. Locking lever

Lift the lever to release and reposition the ballhead. Press the lever down to the side of the ballhead to lock the ballhead in place.

9. 360° panoramic scale

Use the pan scale to accurately set up panoramic photographs and camera pan shots.