


Accessories



Light × 1



Adapter × 1



White Diffuser × 1




Manual × 1

Upon receiving the package, please check whether all the items are included. If there are any missing or broken items, please contact Neewer Customer Service.

Introduction to Functions

EN




When the battery level is running low, the "power Indicator" will start to flash. Please replace the battery as soon as possible.

Introduction to Functions

Mode Instructions

EN



Mode 1: CCT

Long press to turn on the light, rotating the knob to adjust brightness.

Mode 2: HSI

Short press once and rotate the knob to adjust hue brightness.

Mode 3: SCENE

Short press twice and rotate the knob to adjust scene mode brightness.

⚠ There is limited functionality when the Bluetooth is inactive, only allowing the adjustment of brightness/switch mode/power on/off. After successfully connecting to the app, additional modes can be set using the application.

It is not possible to adjust the channel of the LED Video Light.


Introduction to Functions

Available Scenes are as follows:

- | | | |
|----------------|-----------------|---------------|
| (A) Police car | (A) Fireworks | (A) Lightning |
| (B) Ambulance | (B) Party | (B) Paparazzi |
| (C) Fire truck | (C) Candlelight | (C) Screen |


Power Supply

Via DC adapter




Power Supply

Via battery



Compatible battery types


Control The LED Light Via APP




The "NEEWER" APP can be used to control the light through the Bluetooth feature of your mobile. Scan the <APP Guide> QR code on the APP cue card for more details.

When "❄" stops flashing, it indicates that the Bluetooth connection has been established.


Installation Steps




- ① Threaded screw
- ② Angle adjustment knob
- ③ Locking nut



Rotate ① threaded screw into the light body until it is snug.



Insert the base of the light into the camera's and tighten the ③ locking nut. Once secure, the angle can be adjusted using the ② angle adjustment knob.



Insert the white diffuser into the designated slot.

Warning

1. Please do not use or store the item if the ambient temperature exceeds 40°C.
2. Please do not stare at the light directly while it is in use to reduce the risk of visual impairment.
3. Please do not use the item in the rain or in damp conditions.
4. Please do not expose the item to the sun for long periods.
5. Please do not dismantle or modify the circuit of the item.
6. Please turn off the item when not in use.
7. Android smartphones require the GPS to be active prior to use.
8. Please do not cover the heat dissipation holes on the item with cloth or other items to prevent the risk of product damage.
9. Failure to comply with the operation procedures and warnings listed in the manual will void the warranty.

Product Specifications

Model	RGB176
LEDs	176
CRI	>95
Brightness range	0-100
Saturation	0-100
Hue	0-360
Color temperature	3200-5600k
Input voltage	DC 6.5V~17V
Power	8W
Weight	Approx.158g
Dimensions	145*95*40mm