

Overview

HP Stream 11 Pro G3 Notebook PC



Front

- | | | | |
|----|--|-----|--------------------------------------|
| 1. | WLAN antenna | 7. | Power LED |
| 2. | Microphone | 8. | Headphone / Microphone in Combo Jack |
| 3. | Webcam LED | 9. | USB 2.0 Port |
| 4. | Webcam | 10. | Security lock slot |
| 5. | Internal Speakers (2) | 11. | Power Button |
| 6. | Clickpad with multi-touch gestures support | | |

Overview



- 1. HDMI Port
- 2. USB 3.0 Port
- 3. microSD Card Reader

Right

- 4. AC plug LED
- 5. AC adapter plug

Overview

At A Glance

- Pre-installed with Windows 10 editions
- Powered by Intel® Celeron® N3060 processor
- 11.6" diagonal HD WLED anti-glare (1366x768) display
- Storage options with eMMC configurations up to 64 GB to run programs locally
- Memory options up to 4GB for enhanced memory management
- Intel® Dual Band Wireless - AC 7265 802.11 ac (2x2) WiFi + Bluetooth® 4.2 Combo
- Weight starting at 1.10 kg (2.57 lbs) 1.8 cm (0.71 in) thin
- HDMI port for connecting to high-resolution displays
- HP Webcam VGA camera with integrated microphone
- Enhanced security TPM 2.0 discrete chip
- Battery life up to 10 hours and 45 minutes¹

NOTE 1: (Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.)

NOTE: See important legal disclosures for all listed specs in their respective features sections.



Features

PRODUCT NAME

HP Stream 11 Pro G3 Notebook PC

OPERATING SYSTEM

Preinstalled

Windows 10 Pro 64¹
Windows 10 Pro 64 (National Academic only)¹

1. Not all features are available in all editions or versions of Windows of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>.
-

PROCESSORS

Intel® Celeron® N3060 with Intel HD Graphics 400 (1.6 GHz, up to 2.48 GHz, 2 MB cache, 2 cores)¹

1. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering is not a measurement of higher performance. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering is not a measurement of higher performance.
-

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

Intel® HD¹ Graphics 400

Support HD Decode, DX11, and HDMI 1.4b

1. HD content required to view HD images.
-



Features

DISPLAY

Internal

(29.4 cm) 11.6" diagonal HD¹ SVA LED anti-glare(1366x768)

External

Up to 32-bit per pixel color depth

HDMI²

1.4v supports up to 1920 x 1080 @ 60 Hz

1. HD content required to view HD images.
2. HDMI cable sold separately.

NOTE: Resolutions are dependent upon monitor capability, and resolution and color depth settings.

STORAGE AND DRIVES

Primary Storage

eMMC Configurations

32 GB

64 GB

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 980 MB (for Windows 10) is reserved for system recovery software.

MEMORY

Standard

DDR3L-1600 (Transfer rates up to 1600 MT/s)

Single Channel Support (For 2 GB)

Dual Channel Support (For 4 GB)

On board (Customer non-accessible)

2 GB (256 MB x 16 x 4 pcs)

4 GB (256 MB x 16 x 8 pcs)¹

1. Not available with 32 GB eMMC

Maximum

4 GB

Dual-channel

Maximized dual-channel performance requires on board memory design of the same size and speed in both memory slots.

Features

NETWORKING/COMMUNICATIONS

Wireless¹

Intel® Dual Band Wireless - AC 7265 802.11 ac (2x2) WiFi + Bluetooth® 4.2 Combo

Internal Card Expansion

One M.2 slot for WLAN

1. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.

AUDIO/MULTIMEDIA

Audio

Two integrated stereo speaker

Headphone / microphone in combo jack

Webcam¹

VGA camera

Fixed (no tilt) + activity LED, 1 PC, USB 2.0, M-JPEG

640x480 by 24 frames per second

Single digital microphone with noise suppression

HP Noise Cancellation support

1. Internet access required.
2. HD content required to view HD images.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

Full sized black textured

Island-style keyboard (No numeric keypad)

Clickpad

Clickpad with image sensor

Multitouch gestures enabled

Default on: 2-finger scroll, pinch, rotate, 2-finger click, 3-finger flick

Support modern Trackpad gestures

Taps enabled as default



Features

SOFTWARE AND SECURITY

Software

Buy Office¹

Optional HP Touch Point Manager ²

HP ePrint³

HP Support Assistant⁴

HP JumpStart

Security

Lock slot (Lock sold separately)

TPM 2.0

McAfee Checkbox

McAfee LiveSafe⁵

1. Sold separately or as an optional feature.
 2. HP Touchpoint Manager requires purchase of a subscription and supports Android™, iOS and Windows 7 or higher operating systems and PCs, notebooks, tablets and smartphones from various manufacturers. Not available in all countries see www.hp.com/touchpoint for availability information.
 3. HP ePrint requires an internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see www.hp.com/go/businessmobileprinting).
 4. Internet access required.
 5. Internet access required to receive updates. First update included. Subscription required for updates thereafter.
-

POWER

Power Supply

HP 45W Smart AC adapter

Primary Battery

HP 2-cell (37 Whr) Polymer battery

Support battery fast charge

Battery life¹

Up to 10 hours and 45 minutes¹

System Standby Time²

TBD

1. Windows 10 MM14Battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.
 2. Standby life will vary depending on various factors including battery, Memory, CPU, EC and LAN chip. The maximum capacity of the battery will naturally decrease with time and usage.
-

WEIGHTS & DIMENSIONS



Features

Weight

Starting at 2.57 lbs (1.17 kg)

Dimensions (w x d x h)

30.0 x 20.56 x 1.8 cm

11.81 x 8.09 x .71 in

NOTE: Weight varies by configuration and components.



Features

PORTS/SLOTS

Ports

USB 3.0 Ports – One (Right side)

USB 2.0 Ports – One (Left side)

USB 2.0/3.0 Allocation:

2 for the unit

1 for Camera

1 for WLAN Combo

1 AC Smart Pin adapter plug

HP Multi-Format Digital Media Reader

Support micro SD/SDHC/SDXC up to UHS-104 (up to 2TB)

Push-Push Insertion/Removal

NOTE: All cables are sold separately.

SERVICE AND SUPPORT

HP 1 year limited warranty. 1 year limited warranty on primary battery. On-site service and optional extended service contracts are also available. Optional¹ HP CarePacks² are extended service contracts which go beyond your standard limited warranties. For more details, visit: <http://www.hp.com/go/lookuptool>.

1. Sold separately or as an optional feature.
 2. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.
-



Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	Nominal Operating Voltage	19.5V
	Average Operating Power	
Temperature	Max Operating Power	< 45W
	Operating	41° to 95° F (5° to 35° C)
Relative Humidity	Non-operating	-4° to 140° F (-20° to 60° C)
	Operating	10% to 90%, non-condensing
Shock	Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
	Operating	40 G, 2 ms, half-sine
Random Vibration	Non-operating	200 G, 2 ms, half-sine
	Operating	0.75 grms
Altitude (unpressurized)	Non-operating	1.50 grms
	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Planned Industry Standard Certifications	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
	UL	Yes
	FCC Compliance	Yes
	ENERGY STAR®	Yes
	EPEAT	Yes
	ICES	Yes
	Australia / NZ A-Tick Compliance	Yes, now for "RCM"
	CCC	Yes
	Japan VCCI Compliance	Yes
	KC	Yes
	BSMI	Yes
	CE Marking Compliance	Yes
	BNCI or BELUS	Yes, now call "CU" or "EAC"
	CIT	No idea
	GOST	Yes, now call "CU" or "EAC"
	Saudi Arabian Compliance (ICCP)	Yes
	SABS	Yes
	UKRSERTCOMPUTER	Yes

Technical Specifications

DISPLAYS

11.6" diagonal HD WLED Anti-Glare (1366x768) flat (3.6mm), SVA	Outline Dimensions (W x H x D)	278.5 x 168.5 x 3.6mm max.
	Active Area	256.125 x 144.0mm typ.
	Weight	235g max.
	Diagonal Size	11.6 inch
	Contrast Ratio	300:1
	Refresh Rate	60Hz
	Brightness	220nits typ.
	Pixel Resolution	Format 1366 x 768
	Pixel Resolution Interface	Configuration RGB Stripe
	LCD Mode	eDP
	PPI	TN
	Viewing Angle	135
		40/40/15/30

NETWORKING/COMMUNICATIONS

Intel® Dual Band Wireless - AC 7265 802.11 ac (2x2) WiFi + Bluetooth® Combo	Wireless LAN Standards	IEEE 802.11a
		IEEE 802.11b
		IEEE 802.11g
		IEEE 802.11n
		IEEE 802.11ac
	Interoperability	Wi-Fi certified
	Frequency Band	802.11b/g/n

- 2.402 – 2.482 GHz
- Note:

The FCC has declared as of January 1, 2015 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

802.11a/n

- 4.9 – 4.95 GHz (Japan)
- 5.15 – 5.25 GHz
- 5.25 – 5.35 GHz
- 5.47 – 5.725 GHz



Technical Specifications

	5.825 – 5.850 GHz Note: Indonesia no support this band)
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security¹	- IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only - AES-CCMP: 128 bit in hardware 802.1x authentication - WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. - WPA2 certification - IEEE 802.11i - Cisco Certified Extensions, all versions through CCX4 and CCX Lite - WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	802.11b : +16dBm minimum 802.11g : +14dBm minimum 802.11a : +14dBm minimum 802.11n HT20(2.4GHz) : +13dBm minimum 802.11n HT40(2.4GHz) : +13dBm minimum 802.11n HT20(5GHz) : +12dBm minimum 802.11n HT40(5GHz) : +12dBm minimum 802.11ac 80MHz(5GHz) : +11dBm minimum
Power Consumption	Transmit: 2.0 W (max) Receive: 1.6 W (max) Idle mode (PSP): 180 mW (WLAN Associated) Idle mode: 60 mW (WLAN unassociated) Radio disabled: 30 mW



Technical Specifications

Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity³	802.11b, 1Mbps : -94dBm maximum 802.11b, 11Mbps : -86dBm maximum 802.11g, 6Mbps : -88dBm maximum 802.11g, 54Mbps : -74dBm maximum 802.11a, 6Mbps : -86dBm maximum 802.11a, 54Mbps : -72dBm maximum 802.11n, MCS07 : -69dBm maximum 802.11n, MCS15 : -66dBm maximum 802.11ac, 1SS, MCS-0 : -86dBm maximum 802.11ac, 1SS, MCS-9 : -61dBm maximum 802.11ac, 2SS, MCS-0 : -83dBm maximum 802.11ac, 2SS, MCS-9 : -58dBm maximum	
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications	
Form Factor	PCI-Express M.2 MiniCard	
Dimensions	Type 2230: 2.3 x 22.0 x 30.0 mm	
Weight	Type 2230: 2.8g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F (–10° to 70° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)



Technical Specifications

LED Activity

LED Amber – Radio OFF; LED White – Radio ON

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP Integrated Module with Bluetooth 4.0+EDR Wireless Technology

Bluetooth Specification 4.0+EDR Compliant

Frequency Band 2402 to 2480 MHz

Number of Available Channels 79 (1 MHz) available channels

Data Rates and Throughput 3 Mbps data rate; throughput up to 2.17 Mbps

Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric

Transmit Power The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of +4 dBm for BR and EDR.

Receiver Sensitivity	Modulation	0.01% BER	0.001% BER
	GFSK	-80 dBm	-70 dBm
	$\pi/4$ -DQPSK	-80 dBm	-70 dBm

Power Consumption Peak (Tx) 330 mW
Peak (Rx) 230 mW
Selective Suspend 17 mW

Range Up to 33 ft (10 m)

Electrical Interface USB 2.0 compliant

Bluetooth Software Supported Microsoft Windows Bluetooth Software

Link Topology

Electrical Interface Point to Point, Multipoint Pico Nets up to 7 slaves

Full support of Bluetooth Security Provisions



Technical Specifications

Bluetooth Software Supported

Security

Power Management

Microsoft Windows ACPI, and USB Bus Support

Power Management

Self-configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff

Certifications

Security

All necessary regulatory approvals for supported countries, including:

Certifications

FCC (47 CFR) Part 15C, Section 15.247 & 15.249

Bluetooth Profiles Supported

Power Management

ETS 300 328, ETS 300 826

Certifications

Low Voltage Directive IEC950

Certifications

UL, CSA, and CE Mark

Bluetooth Profiles Supported

Serial Port Profile (SPP)¹
 Service Discovery Application Profile (SDAP)
 Dial-Up Networking (DUN)^{1,2}
 Generic Object Exchange Profile (GOEP)^{1,2}
 Object Push Profile (OPP)^{1,2}
 File Transfer Profile (FTP)
 Synchronization Profile (SYNC)
 Hard Copy Cable Replacement (HCRP)^{1,2}
 Personal Area Networking Profile (PAN)^{1,2}
 Human Interface Device Profile (HID)^{1,2}
 FAX Profile (FAX)
 Basic Imaging Profile (BIP)²
 Headset Profile (HSP)
 Hands Free Profile (HFP)
 Advanced Audio Distribution Profile (A2DP)



Technical Specifications

AUDIO/MULTIMEDIA

Hardware	Implementation	Realtek ALC 3227 Low Power High Definition Audio Codec
	Function Key Volume Controls	Volume up, Volume down, and Mute
Audio Output Quality	Full Duplex	Yes
	Microphone In	Mono
	Headphone/Line Out	Stereo
	Integrated Microphone	Yes, Dual Digital Microphone
	Frequency Response	20 Hz – 20KHz
	Signal to Noise Ratio	90 dB FSA (Typical)
	Total Harmonic Distortion	-80 dB FS (Typical)
	Noise Floor	-120 dB
	Play/Record Sampling Rate(s)	8KHz – 96KHz
	DAC	16, 20 or 24 bit
Integrated Stereo Speakers	ADC	16 or 20 bit
	Power Rating	2 Watts
	Impedance	4 Ohm

POWER

HP 45W AC Adapter	Dimensions	3.74 x 1.57 x 1.04 in (9.5 x 4.0 x 2.65 cm)
	Weight	0.386 lb (175g) max
Input	Input Efficiency	87.74% at 115Vac and 88.4% at 230Vac
	Input frequency range	47 to 63 Hz
	Input AC current	1.4A at 90VAC
	Output	45W
	Hold-up time	5m Sec. at 115 VAC input
	DC output	19.5V
	Output current limit	< 8.0A
Environmental Design	Operating temperature	32° to 95° F (0° to 35° C)
	Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
	Altitude	0 to 16,400 ft (0 to 5,000 m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%



Technical Specifications

EMI and Safety Certifications

CE Mark - full compliance with LVD and EMC directives
 * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.
 * MTBF - over 200,000 hours at 25°C ambient condition.

HP 2-cell Polymer Battery Cells/Type (37.69 WHr)

Watt-hour capacity Temperature

2-cell Polymer

37.69Whr

Operating (Charging) 0° to 45° C

Operating (Discharging) -10° to 60° C

Non-operating -20° ~ 60° C (1 month)

-20° ~ 45° C (3 month)

-20° ~ 30° C (6 month)

Warranty

1 year limited

ENVIRONMENTAL

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- EPEAT[®] Gold registered in the United States. See <http://www.epeat.net> for registration status in your country.

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Energy Consumption (in accordance with US ENERGY STAR® test method)

115VAC, 60Hz

230VAC, 50Hz

100VAC, 50Hz

Normal Operation (Sort idle)

5.06 W

5.08 W

5.19 W

Normal Operation (Long idle)

2.78 W

2.83 W

2.78 W

Sleep

0.72 W

0.74 W

0.72 W

Off

0.16 W

0.24 W

0.16 W



Technical Specifications

Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Short idle)	17 BTU/hr	17 BTU/hr	18 BTU/hr
Normal Operation (Long idle)	10 BTU/hr	10 BTU/hr	10 BTU/hr
Sleep	2 BTU/hr	3 BTU/hr	2 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr

*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L _{WAd} , bels)	Sound Pressure (L _{pAm} , decibels)
Typically Configured – Idle	1.7	16
Fixed Disk – Random writes	1.7	16

Longevity and Upgrading This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 3 USB ports
- 1 PC card slot (type I/II)
- 1 ExpressCard/54 slot
- 1 IEEE 1394 Port
- 2 SODIMM memory slots
- Optional expansion base docking station
- 1 multi-bay II storage port
- Interchangeable HDD

Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.

Not all configuration components are available in all regions/countries.
c05201813 — DA — 15647 Worldwide — Version 2 — September 27, 2016



Technical Specifications

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

Mercury greater than 1ppm by weight

Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the <GOLD> level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0.0% post-consumer recycled plastic (by wt.)
- This product is 97.3% recycle-able when properly disposed of at end of life.

Packaging Materials

External: PAPER/Corrugated 292.0 g

Internal: PLASTIC/EPE (Expanded Polyethylene) 34.5 g

The plastic packaging material contains at least 0% recycled content.

The corrugated paper packaging materials contains at least 80% recycled content.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf>):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)



Technical Specifications

- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www8.hp.com/us/en/hp-information/environment/ecolabels.html>

ISO 14001 certificates:

<http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842>

and

<http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf>

COUNTRY OF ORIGIN

China



Options and Accessories (sold separately and availability may vary by country)

Category	Description	Part number
Cases	HP Business Top Load	H5M92AA
	HP Business Slim Top Load	H5M91AA
	HP Business Backpack	H5M90AA
	HP Essential Top Load Case (up to 15.6")	H2W17AA#xxx
Docking	HP USB 3.0 Travel Dock	T0K30AA#AC3
	HP USB 3.0 Port Replicator	H1L08AA#xxx
	HP Display and Notebook Stand II	E8G00AA#xxx
Input/Output	HP Slim USB Keyboard & Mouse	T6T83AA#xxx
	HP USB Optical Travel mouse	G1K28AA
	HP Ultrathin Bluetooth Mouse	L9V78AA
	HP Conferencing Keyboard	K8P74AA#xxx
	HP UC Speaker Phone	K7V16AA
	HP UC Wired Headset	K7V17AA
	HDMI to VGA Adapter	H4F02AA
	HP HDMI to DVI Adapter	F5A28AA
Power	HP USB Gigabit RJ45 Adapter	N7P47AA#xxx
	HP 45W Smart AC Adapter (4.5mm)	H6Y88AA#xxx
	HP 65W Slim AC Adapter	H6Y82AA#xxx
	HP 65W Smart Travel AC Adapter	J0E43AA#xxx
Storage	HP External USB Optical Drive	F2B56AA
Security	HP Keyed Cable Lock 10mm	T1A62AA



Summary of Changes

Date of change:	Version History:	Description of change:
Sep 27 2016	V1 to V2	Environmental Data added

Copyright © 2016 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Pentium and Celeron are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. ENERGY STAR is a registered trademark mark owned by the U.S. Environmental Protection Agency. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation.

