



KRAMER

C-5BM/5BM

5 BNC RGBHV Mini Coax Cable

| 3G HD-SDI - BNC



Kramer's C-5BM/5BM is constructed of 5 mini coax cables in a single jacket with 75 BNC connectors at each end. It offers outstanding quality, durability, and high performance for any RGBHV video signal application

FEATURES

Quality Construction - Constructed from flexible, high quality 5 mini coax cable

Applications - Ideal for routing typical computer graphics video RGBHV signals to display devices such as projectors and monitors

Easy Installation - Breakout length is 18in (0.5m) on any cables 6ft (1.8m) or longer. Shorter cables have approx. 7in (0.18m) breakout length

Varied Selection of Lengths - Available in versions of 3 to 100ft (0.9 to 30.5m)

Cable Specs - For detailed cable specs, see Kramer BC5X



KRAMER

TECHNICAL SPECIFICATIONS

CONSTRUCTION	Coax Center Conductor: 28 AWG 7/36 tinned copper
	Dielectric: Foam polyethylene
	Shield: 90% braid 38 AWG tinned copper
	Coax Jacket Colors: Red, green, blue, yellow, black
	Outer Jacket: PVC
DIAMETERS	Outer Jacket Color: Dark gray with white lettering
	Center Conductor: 0.38mm (0.015in)
	Individual Coax: 2.75mm (0.108in)
Dielectric:	Outside Diameter: 9.2mm (0.362in)
	1.6mm (0.063in)
ELECTRICAL	Impedance: 75
	DC Resistance: 237/km (72.2/1000ft)
	Capacitance: 60pF/m (18.3pF/ft)
	Velocity of Propagation: 78%
	Temperature: 20° to +75°C (4° to +167°F)
	Attenuation (dB/100 ft.): 0.6dB @1MHz
	1.4dB @5MHz
	2.1dB @10MHz
	4.7dB @50MHz
	6.8dB @100MHz
REGULATORY	9.2dB @180MHz
	14.2dB @400MHz
	20.1dB @750MHz
	23.8dB @1000MHz
	UL: CL2
	CSA: C(UL) CL2



KRAMER

CONFIGURATIONS

C-5BM/5BM-3	5 BNC (M) to 5 BNC (M) Cable
C-5BM/5BM-10	5 BNC (M) to 5 BNC (M) Cable
C-5BM/5BM-15	5 BNC (M) to 5 BNC (M) Cable
C-5BM/5BM-25	5 BNC (M) to 5 BNC (M) Cable
C-5BM/5BM-35	5 BNC (M) to 5 BNC (M) Cable
C-5BM/5BM-50	5 BNC (M) to 5 BNC (M) Cable
C-5BM/5BM-75	5 BNC (M) to 5 BNC (M) Cable
C-5BM/5BM-100	5 BNC (M) to 5 BNC (M) Cable